



Applications: Widely used in Offices, Hotels, Schools, Supermarkets, Shopping Malls, etc

Electrical Parameters	
Input Voltage	100-285V AC
Rated Power	36W
Efficiency	>90%
Power Factor	>0.90
Harmonics	<20%

LED Details	
LED Make	BMTC SANAN 3528
No Of LED's	42
Led Viewing Angle	IIO degrees
Colour Temperature (cct)	3000k/4000k/6500k
Lumens	90 Lm/W
Luminous Flux	3240 lm
CRI	>80

Protection Parameters	
Over- Current Protection	Yes
Short- Circuit Protection	Yes
Over-Voltage Protection	Yes
<b>Dust And Water Protection</b>	IP20


Luminary Housing Details	
Body	GP Sheet Back Panel
Frame	ABS Front Frame
Diffuser	PC Cover

Certifications	
BIS	Tested and Approved by BIS
ROHS	Yes

## **Features**

- Super bright output indoor lights
- Equipped with non- flickering drivers & high lumens SMDLED chip with lens
- Long life span up to 50k hours, low decay & low maintenance
- Trim-less ABS frame with zero light leakage
- High efficiency PMMA & even light distribution
- Easy installation Spring fastener, Ceiling Suspension, Surface mounting and Grid mounting
- Dimmable driver supports for all products

## **Installation Types**





## Light distribution:-

