



Model: MB-14585-4-30W

Applications: Widely used in Commercial Lighting, Airports, Office Spaces, Educational Institutes, Hotels and Restaurants, Retail Shops, Showrooms and Malls, Banks.

| Electrical Parameters | |
|------------------------------|-------------|
| Input Voltage | 100-285V AC |
| Rated Power | 30VV |
| Efficiency | >90% |
| Power Factor | >0.90 |
| Harmonics | < 10% |

| LED Details | |
|--------------------------|-------------|
| Mounting Type | Recess |
| Led Viewing Angle | 120 degrees |
| Colour Temperature (cct) | 4000k/6000k |
| Lumens | I00 Lm/W |
| Luminous Flux | >3000 lm |
| CRI | >80 |

| Protection Parameters | |
|------------------------------|-----|
| Over- Current Protection | Yes |
| Short- Circuit Protection | Yes |
| Over-Voltage Protection | Yes |

| Luminary Housing Details | |
|--------------------------|----------------|
| Body | CRCA enclosure |
| IP Rating | IP20 |
| Diffuser | PS |

Features

- Super bright output indoor lights
- Equipped with non- flickering drivers & high lumens SMDLED chip
- Long life span up to 50k hours, low decay & low maintenance
- High grade CRCA Body with Quality powder coated surface
- Zero light leakage
- High efficiency PMMA & even light distribution
- Dimmable driver supports for all products

LUMINOUS INTENSITY DISTRIBUTION







